

Density	$\rho = \frac{m}{V}$	ρ (rho) = density (kg/m ³ or g/cm ³) m = mass (kg or g) V = volume (m ³ or cm ³)	s-t graph	Area under s-t graph = distance	Area of trapezium = $\frac{1}{2} \times (a+b) \times h$ a and b are parallel sides
Constant Speed (only)	$s = \frac{D}{t}$	S = speed (m/s) D = distance (m) t = time (s)	Pressure	$p = \frac{F}{A}$	P = pressure (Pa=Pascal or N/m ²) F = force (N) A = area (m ²)
Average speed	$average\ speed = \frac{Total\ distance}{Total\ time}$	Average speed = $(u + v)/2$ u = initial speed (m/s) v = final speed (m/s)	Pressure in liquid	$p = \rho \times g \times h$	ρ = density (kg/m ³) g = gravity = 10 m/s ² h = height or depth (m)
Acceleration	$a = \frac{v - u}{t}$	a = acceleration (m/s ²) u = initial velocity (m/s) v = final velocity (m/s)	Boyle's law	$p_1 \times V_1 = p_2 \times V_2$	P = pressure(Pa) V = volume(m ³)
Newton's 2nd law	$F = m \times a$	F = force (N) m = mass(kg) a = acceleration (m/s ²)	Charles' law	$\frac{V_1}{T_1} = \frac{V_2}{T_2}$	V = volume(m ³) T = temperature(K=Kelvin)
Weight	$W = m \times g$	W = weight (N) g = gravity (m/s ²) = 10 m/s ² m = mass (kg)	Pressure law	$\frac{p_1}{T_1} = \frac{p_2}{T_2}$	P = pressure(Pa) T = temperature(K)
Moment	$Moment = F \times d$	F = Force (N) d = perpendicular distance from pivot (m or cm)	Gas law	$\frac{p_1 \times V_1}{T_1} = \frac{p_2 \times V_2}{T_2}$	P = pressure(Pa) T = temperature(K) V = volume(m ³)
principle of moment	$M_{clockwise} = M_{anticlockwise}$		Work done	$W = F \times d$	W = work done (J=joule) F = force(N) d = distance moved in direction of force (m)
Momentum	$p = m \times v$	p = momentum (kgm/s) m = mass (kg) v = velocity (m/s)	Specific Heat capacity	$Q = m \times c \times \Delta T$	Q = heat energy(J) m = mass(kg) c = specific heat capacity(J/kg C°) ΔT = change in temperature (C°)
Impulse	$I = mv - mu = Ft$	I = Impulse (Ns or kgm/s) m = mass (kg) u = initial velocity (m/s) v = final velocity (m/s) F = Force (N) t = time (s)	Specific Latent heat	$Q = m \times L$	Q = heat energy (J) m = mass(kg) L = specific latent heat (J/kg)
D-t graph	Gradient of D-t graph = speed		Thermal Capacity	$C = \frac{Q}{\Delta T}$	Q = heat energy(J) C = Thermal capacity(J/C°) ΔT = change in temperature (C°)
s-t graph	Gradient of s-t graph = acceleration		Gravitational potential energy	$GPE = m \times g \times h$	GPE = gravitational potential energy (J) g = gravity (10 m/s ²) h = height (m)

Kinetic energy	$KE = \frac{1}{2}mv^2$	KE = kinetic energy(J) m = mass(kg) v = velocity(m/s)
Power	$P = \frac{E}{t}$	P=power (W=Watt or J/s) E = energy or Work done(J) t = time(s)
Efficiency	$Eff = \frac{E_{out}}{E_{in}} = \frac{P_{out}}{P_{in}}$	E _{out} = useful energy output (J) E _{in} = energy input(J) P _{out} = power output(W) P _{in} = power input(W)
Frequency	$f = \frac{1}{T}$	f = frequency(Hz=hertz) T = time period(s)
Wave equation	$v = f \times \lambda$	v = velocity of wave (m/s) f = frequency (Hz) λ(lambda) = wavelength (m)
Refractive index (no unit)	$\frac{n_2}{n_1} = \frac{\sin \theta_i}{\sin \theta_r}$	n ₁ = refractive index in medium 1 n ₂ = refractive index in medium 2 θ _i = angle of incidence θ _r = angle of refraction refractive index in air = 1
Refractive index (n)	$n = \frac{\text{speed of light in vacuum}}{\text{speed of light in medium}}$	speed of light in vacuum = 3×10 ⁸ m/s ≈ in air
Critical angle	$\sin \theta_c = \frac{1}{n}$	θ _c = critical angle n = refractive index
Current (I)	$I = \frac{Q}{t}$	I = current (A or C/s) Q = charge (C=coulomb) t = time (s)
Voltage or Potential Difference (V)	$V = \frac{E}{Q}$	V = voltage or Potential Difference (V or J/V) E = energy (J) Q = charge (C)
Ohm's law	$V = I \times R$	V = voltage(V) I = current(A) R = resistance (Ω = Ohm)

Electrical Power

$$P = V \times I$$

$$P = I^2 \times R$$

$$P = \frac{V^2}{R}$$

$$E = VIt$$

P = Power (W or J/s)
V = Voltage (V)
I = Current (A)
R = Resistance (Ω)
t = time (s)

Combine resistance in series circuit

$$R_T = R_1 + R_2 + R_3 \dots$$

Combine resistance in parallel circuit

$$\frac{1}{R_T} = \frac{1}{R_1} + \frac{1}{R_2} + \frac{1}{R_3} \dots$$

Don't forget to flip it back.
For 2 resistors

$$R_T = \frac{R_1 \times R_2}{R_1 + R_2}$$

Transformer

$$\frac{n_1}{n_2} = \frac{V_1}{V_2}$$

n₁ = no. of turns in primary
n₂ = no. of turns in secondary
V₁ = voltage input
V₂ = voltage output

Transformer (Efficiency 100%)

$$P_{in} = P_{out}$$

$$I_1 \times V_1 = I_2 \times V_2$$

I₁ = current input(A)
I₂ = current output(A)
V₁ = voltage input(V)
V₂ = voltage output(V)



Quint School Team
Tel. 099 415 4935
Line ID: school.quint
IG: School.Quint
Fan Page: Quint School
Fortune town, G floor, Education zone